



135 PSI

10.4 SCFM @ 90 PSI
3hp / 60 GALLON

cast iron pump

PORTER-CABLE

240 VOLT





ROLAIR
SYSTEMS



INPUT
SERIAL NO. KC313117
STOCK NO. 613441

VOLTS	100/240/115
AMPERES	160/70/4
KW	
PHASE	1 HERTZ 60



EVIDENCE OF LABEL TRANSFERRED VOID WARRANTY



105-300

90-265

AC

DC

35-165

35-155

RATED OUTPUT

	AC	DC	AC	DC
VOLTS	30	35	25	28
AMPERES	160	70	200	200
DUTY CYCLE	20%	30%	71	70
MAX. OCV	70	70		

NEMA CLASS II ISO



Dialarc® 250 AC/DC

CONSTANT CURRENT AC/DC ARC WELDING POWER SOURCE

POWER

OFF

CBT

DC POSITIVE



WARNING

ELECTRIC SHOCK CAN KILL.
• Do not touch live parts or moving parts of the machine.
• Do not touch the electrode holder or electrode while the machine is on.
• Do not touch the electrode holder or electrode while the machine is on.





Miller 212 Auto-Set

MATERIAL THICKNESS
1/8" 3/16" 1/4" 3/8"
10 12 14 16 18 20 22
VOLTAGE

WIRE SPEED
1 20 30 40 50 60 70 80 90 100
WELD WIRE DIAMETER
0.030" 0.035"



FOR YOUR SAFETY
Material Safety
Data Sheets - MSDS

SAFETY
FIRST
FIRST AID
STATION

RANGER

LINCOLN
ELECTRIC





Order Mail
Box Bryo
in


Miller

WARNING: ELECTRIC SHOCK
DO NOT TOUCH THE WELDING TERMINALS
OR OTHER EXPOSED ELECTRICAL PARTS
WHEN THE MACHINE IS PLUGGED INTO THE
POWER SOURCE.



Millermatic
212 Auto-Set

 **Miller**







ULTRA PRO

8" BENCH GRINDER Touret d'établi 8 po.

No Load Speed	3600 RPM
Régime libre	3600 tr/min.
Arbor Hole / Arbre	5/8"
Wheel Diameter / Diamètre de meule	8"
Wheel Thickness / Épaisseur de meule	1"
Electrical Rating / Caractéristiques électriques	
Voltage / Tension	120
Amps / Ampères	3.5
Hz	60

Model No. / No. de modèle: 70118

Serial No. / No. de série: 151400115

UL CONFORMS TO UL STD 987
Conforme au norme UL STD 987
Imported by / Importé par: UAP Inc. Montreal (Quebec) H1N 2B5



