




Building 2
contents
Aprox. 20
pails of semi-
synthetic WL
grease injector
oil

Building 2

High base Semi-Synthetic extra inhibited Wireline grease injector oil

High Base Semi Synthetic EXTRA INHIBITED

Wire Line Injector Sealant and Lube

Added Resistance To CO₂, H₂S, Production Acids
Salt Water, Circulating Fluids and Chemicals.
Extra Wire Line and Injector Head Protection

Wider Working Temperature Range
Pour Point of -45°C

Lowest Working Temperature -43°C
Viscosity 33 cSt at 40°C Approximate
Extra Lubrication For Minimal Drag and Twisting

Extra Lubrication For Minimal Drag and Twisting
Stronger Packing For Better Dynamic Seal

Easy Cleanup with Chemmex Biodegradable C3

LOT# 08-11-2011
Supersaul Chemmex Inc.
PH 780-967-4031 FAX 780-967-5174

LIGHT
Minimum 80% Synthetic

Environment Friendly

User Friendly

TDG: Not Regulated MSDS Available
WHMIS: Not Controlled
HEALTH AND FIRST AID
INGESTION: Large amounts may
irritate the intestinal tract.

First Aid: Normally not needed.
SKIN: Prolonged contact may irritate
the skin.

First Aid: Wash with soap and water.
Launder clothing.

EYES: May irritate the eyes.
First Aid: Rinse with lots of water.

INHALATION: Mist may irritate the
respiratory system. This product tends
not to mist.

First Aid: Remove from exposure. Seek
help if required.